



M 1 2 9 7

2 doors
1700 x 800 x 900 mm
Weight: 180 kg

M 1 2 9 8

3 doors
2240 x 800 x 900 mm
Weight: 195 kg

M 1 2 9 9

4 doors
2780 x 800 x 900 mm
Weight: 215 kg

EN

Digital temperature control (-2/26° C)
Equipped with air humidity control for chocolate
Interior in stainless steel
Grids included (6 per door)
60 mm polyurethane insulation (density 45 kg/m³)
Doors close automatically, pressure on the frame is adjustable
Ventilated evaporator
Automatic evaporation of defrost water
Adjustable top-piece, 150 mm
Non-cooled multi-purpose drawer
Power: 220 V - 50 Hz
(other voltages on request) single-phase AC

ES

Control digital de temperatura (-2/26° C)
Equipada con control de humedad para chocolate
Interior en acero inoxidable
Rejillas incluidas (6 por puerta)
60 mm aislamiento poliuretano (densidad 45 kg/m³)
Las puertas se cierran automáticamente, la presión en el soporte se puede ajustar
Evaporador ventilado
Evaporación automática del agua deshelada
Parte superior ajustable, 150 mm
Cajón no refrigerado polivalente
Electricidad: 220 V - 50 Hz
(otras tensiones disponibles bajo pedido)
Corriente alterna monofásica

