

Construction of the oven

- External structure of the oven built in stainless steel AISI 430.
- Chambers independent of each other and with thick rock wool insulation.
- Electrical elements armored.
- Doors built with low emission LOW-e glass.
- Steam producer of great capacity and quick recovery.
- ECO-ENERGETIC design.



Cooking quality

- Distribution of the shielded electric resistances to obtain a uniform and quality cooking.
- Large surface heat emission ceiling and floor of each chamber.
- Independent control of roof, floor and mouth resistances.
- Refractory stone of alimentary grade to give a spectacular sole to the final product.
- High thermal mass. Oven temperature very stable over time.



600 mm DOORS									
Type	Power	No. of Doors per camera	Cooking surface (m2)	Dimensions int.(mm)		Dimensions ext. (mm)		Hight (mm)	weight (kg)
				Width	depth	Width	depth		
OVEN TO 3 CAMERAS									
ELECSOL 3C/1P 160	16.8	1	3	620	1.600	1.260	2.723	2.200	1.760
ELECSOL 3C/1P 200	19.3		3.70		2.000		3.123		1.960
ELECSOL 3C-1A/1P 160	16.8		3		1.600		2.723		1.760
ELECSOL 3C-1A/1P 200	19.3		3.70		2.000		3.123		1.960
ELECSOL 3C/2P 160	25.5	2	6	1.240	1.600	1.880	2.723	2.200	2.330
ELECSOL 3C/2P 200	29.7		7.4		2.000		3.123		2.600
ELECSOL 3C/2P 240	33.9		9		2.400		3.523		2.890
ELECSOL 3C-1A/2P 160	25.5		6		1.600		2.723		2.330
ELECSOL 3C-1A/2P 200	29.7		7.4		2.000		3.123		2.600
ELECSOL 3C-1A/2P 240	33.9		9		2.400		3.523		2.890
ELECSOL 3C/3P 160	34.5	3	9	1.860	1.600	2.500	2.723	2.200	2.910
ELECSOL 3C/3P 200	40.5		11.2		2.000		3.123		3.270
ELECSOL 3C/3P 240	46.5		13.4		2.400		3.523		3.640
ELECSOL 3C-A1/3P 160	34.5		9		1.600		2.723		2.910
ELECSOL 3C-A1/3P 200	40.5		11.2		2.000		3.123		3.270
ELECSOL 3C-A1/3P 240	46.5		13.4		2.400		3.523		3.640
OVEN TO 4 CAMERAS									
ELECSOL 4C/1P 160	22.4	1	4	620	1.600	1.260	2.723	2.200	2.090
ELECSOL 4C/1P 200	25.7		5		2.000		3.123		2.310
ELECSOL 4C/1P 240	29		6		2.400		3.523		2.530
ELECSOL 4C/2P 160	34	2	8	1.240	1.600	1.880	2.723	2.200	3.090
ELECSOL 4C/2P 200	39.6		10		2.000		3.123		3.410
ELECSOL 4C/2P 240	45.2		12		2.400		3.523		3.460
ELECSOL 4C/3P 160	46	3	12	1.860	1.600	2.500	2.723	2.200	3.460
ELECSOL 4C/3P 200	54		15		2.000		3.123		3.910
ELECSOL 4C/3P 240	62		18		2.400		3.523		4.350
800 mm DOORS									
OVEN TO 3 CAMERAS									
ELECSOL 3C/1P80 160	19.5	1	4	820	1.600	1.460	2.723	2.200	1.960
ELECSOL 3C/1P80 200	22.5		5		2.000		3.123		2.180
ELECSOL 3C/2P80 160	34.5	2	7.9	1.640	1.600	2.280	2.723	2.200	2.690
ELECSOL 3C/2P80 200	40.5		9.9		2.000		3.123		3.030
ELECSOL 3C/2P80 240	46.5		11.9		2.400		3.523		3.360
OVEN TO 4 CAMERAS									
ELECSOL 4C/1P80 160	26	1	5.3	820	1.600	1.460	2.723	2.200	2.320
ELECSOL 4C/1P80 200	30		6.6		2.000		3.123		2.570
ELECSOL 4C/1P80 240	34		7.9		2.400		3.523		2.840
ELECSOL 4C/2P80 160	34.6	2	10.5	1.640	1.600	2.280	2.723	2.200	3.220
ELECSOL 4C/2P80 200	54		13.16		2.000		3.123		3.610
ELECSOL 4C/2P80 240	62		15.8		2.400		3.523		4.010



SALVA INDUSTRIAL S.L.

GI-636 Km. 6 Polígono 107 • 20100 Lezo, Guipúzcoa

Tel: (+34) 943 449300

e-mail España: salva@salva.es

e-mail Export: sales@salva.es

www.salva.es

Reserved the right to modify the design or measurements. It hasn't contractual value