

HTY505DAUS

Family	Dishwasher
Subfamily	Hoodtype dishwasher
Basket dimensions	500x500 mm
Panel	Ecoline 2016
Drain pump with 3 stage filter system	Yes
Rinse pump H.T.R. system	Rinse pump with atmospheric boiler
Usable load height	440 mm
Power connection	400 V 3N~ / 16 A / 9,7 kW / 50 Hz
Product dimensions WxDxH	620x736x1530 mm



Distribution

Solutions	Bars/Cafes; Hotels; Restaurants/Catering; Butcher's shops; Schools; QSR
-----------	--

Aesthetics

Serie	Ecoline	Led color	Red
Control panel	Electronic		

Functions



Functionality	GN 1/1 trays washing; Triple filter; HTR; Door clearance 440mm
---------------	--

Programs

Programs		
Boiler 85°C/Tank 60°C-1'30"	Boiler 85°C/Tank 60°C-2'30"	Boiler 85°C/Tank 60°C-4'
Drain and self cleaning cycle	Yes	
Maximum basket/hour	40	
Maximum dishes/hour	720	

Interface

Display	4 digit	Cycle progress alert	Yes
Number of buttons	5	End-cycle alert	Yes
On/Off button	Yes	Manual diagnostic	Yes

Construction

Tank	Deep drawn	Hood	Single wall
Tank construction	Double wall	Tank capacity	14 l
Tank material	Stainless steel AISI 304	Boiler capacity	8 l
Back panel	Prepainted	Protection class	IPX4
Tank filter	Stainless steel	Net weight	108,000 kg
Washing spray arm	Stainless steel	Drain max. height	1000 mm
Rinse spray arm	Stainless steel		

Technical Features

Tank heating element	2200 W	Water inlet	Cold 15°C
Boiler heating element	9000 W	Max temperature inlet water	60°C
Washing pump	700 W	Max water hardness	12°FH - 7°dH
Default connection	9700 W	Water inlet	Cold 15°C
Water cycle consumption	2,7 l		

Electrical Connection

Plug	Not present	Electrical connection option	230 V~ / 29 A / 6,7 kW / 50 Hz; 400 V 3N~ / 13 A / 6,7 kW / 50 Hz
-------------	-------------	-------------------------------------	---

Equipments

Peristaltic detergent doser	Yes, electronic control	Cycle counter	Yes
Peristaltic detergent doser	Yes, manual	Default chemicals dosing unit of measure	gr/l
Peristaltic rinse-aid doser	Yes, electronic control	Break tank	Yes
Detergent load	Yes, manual	Partial renewal of water in the tank and built-in drain pump	Si
Peristaltic detergent doser	Yes, manual	Water supply pipe diameter	16 mm
Rinse load	Yes, manual	Drain supply pipe diameter	21,5 mm
Soft Start	Yes	Automatic start	Yes, default OFF
Boiler thermostop	Yes default ON	Trays washing option GN1/1 530x325mm	Yes

Accessories Included

Dish basket	PB50D01	Water supply pipe	In acciaio Watermark
Cutlery basket	PHOOS02	Drain pipe	Yes - 2m
Flat basket	1x PB50G02		

Not included accessories



WT5700SR

Entry table right side 700mm



WT51200SR

Entry table right side 1200mm



WT5700SL

Entry table left side 700mm



WH00S01

Wire insert for 12 small dishes



WTX5700R

Exit table right side 700mm



WTX51200L

Exit table left side 1200mm



WB50G01

Universal wire basket with flat bottom
500x500



PB50D01

Basket made of polypropylene for 18 plates
500x500



WTX51200R

Exit table right side 1200mm



WTX51200

Exit table both sides 1200mm



PHOOS03

Basket in polypropylene with 6
compartments for cutlery for Capote



WT51200SHL

Entry table left side 1200mm



PHOOS01

Single basket in polypropylene for
cutlery



WB50T02

Wire basket for 5 trays 600x500



WT51200SHR

Entry table right side 1200mm



WT51200SL

Entry table left side 1200mm



WB50G02

Wire basket for glasses with inclined
bottom 500x500



PB50G01

Universal basket in polypropylene
500x500



WB50G04

Wire basket for glasses with inclined bottom 500x500



WTX5700

Exit table both sides 700mm



PHOOS02

Basket in polypropylene for cutlery with 6 compartments



WB50D01

Wire basket for 18 dishes and trays 500x500



WB50G03

Wire basket for glasses with inclined bottom 500x500



WTX5700L

Exit table left side 700mm

Symbols glossary (TT)

