

UD511MDAUS

EASYLINE **FULLY INSULATED** UNDERBENCH DISHWASHER - 1.5 AMP

500x500 mm basket



GUARANTEED WASH PERFORMANCE

In commercial dishwashers, the rinse is the most important part of the wash cycle, as it is the only one performed with clean water. This is the reason why, at Smeg, we believe all commercial dishwashers must have **a rinse pump on board**, the only way to guarantee that optimal and constant pressure and temperature are maintained throughout the rinse cycle.

WE BELIEVE IN OUR QUALITY

All dishwashers are manufactured in our state of the art factory in Italy, where we monitor all phases of design, engineering and production.



PRODUCT FEATURES

- **Double skin construction in AISI 304 stainless steel**
- Moulded wash tank, rack guides and door
- **Counterbalanced door with spring assisted hinges, full surround door gasket and no supporting rods**
- **HTR (High Temperature Rinse) system with atmospheric boiler and rinse pump**
- 2.5 litres water rinse cycle
- Over 22% water exchange every cycle
- Drain pump with triple stage dynamic filtration system
- **Door opening height: 415mm**
- Upper and lower wash and rinse arms in AISI 304 stainless steel
- Full size tank filter with removable basket, all in AISI 304 stainless steel
- Electronic controls with 3 wash programs
- Shortest wash program 90 seconds
- Soft start wash pump
- Automatic self-cleaning cycle
- Shut-off at the end of drain cycle
- Thermostop system to ensure correct rinse temperature
- Adjustable peristaltic pumps for detergent and rinse-aid injection
- Self-diagnostic system with error messages
- **15 Amp plug**
- **24 months parts and labour warranty**

ACCESSORIES

- PB50D01 - 500x500mm basket. 18-plate Ø250mm
- PB50G01 - 500x500mm flat-bottomed basket
- WB50D01 - Wire basket. 18-plate Ø250mm
- WB50G01 - Wide-mesh wire basket with flat bottom
- WB50G02 - Wire basket with inclined bottom for stem glasses max Ø90mm
- WB50G03 - Wire basket with inclined bottom for stem glasses max Ø72mm
- WB50G04 - Wire basket with inclined bottom for stem glasses max Ø120mm
- WB50T02 - Wire basket for 7 GN1/1 20mm deep baking rins
- WB50T03 - Wire basket for GN1/1 60mm deep


UD511MDAUS

EASYLINE **FULLY INSULATED** UNDERBENCH DISHWASHER - 1.5 AMP

500x500 mm basket

TECHNICAL SPECIFICATIONS

Dimensions (mm) (WxDxH)	600x600x820	Minimum supply pressure (bar)	2.5
Basket (mm)	500x500	Drain pump	Yes
Door clearance (mm)	415	Rinse aid pump	Peristaltic
Type of interface	electronic	Detergent pump	Peristaltic
Door/hood structure	double skinned insulated	Programme 1 (sec)	90*
Supplied water temperature (°C)	Hot water (max 60°)	Programme 2 (sec)	150*
Tank volume (litres)	11	Programme 3 (sec)	240*
Tank heating element (W)	2,000	Special programmes	Total renewal of the water inside the tank Extra rinse Self-cleaning
Filtering system	Tank filter + selective filter	Thermostop	Yes
Boiler volume (litres)	6	Total power (W)	3,000
Boiler heating element (W)	2,300	Electrical connection	Single Phase 1.5A 230V~/13A/3,0kW/50Hz
Wash pump (W)	700	Basket number	
Tank temperature (°C)	60°	dishes	1 x PB50D01
Rinse pump	Yes	universal / glasses	1 x PB50G01
Rinse temperature (°C)	85°	cutlery	1 x PHOOS02
Adjustable temperatures	Yes		
Water consumption (litres/cycle)	2.5		



CONNECTION WIRING DIAGRAM KEY

R	LOWER BACK PANEL
C	EXTERNAL DISPENSER POWER SUPPLY CABLE ENTRY POINT
S	DRAIN HOSE
Q	EARTHER TERMINAL

P	PERISTALTIC PUMP HOSES
E	ELECTRICITY SUPPLY CABLE

* Supplied water temperature >50°C and <60°C and three-phase electrical connection whenever possible.

* Indicative wash times



UNI EN ISO 9001
9130-Smeg

UNI EN ISO 14001
9191-SME2

DHSAS 18001
9192-SME3